# **FLEXIBLE HOSE**



### **MFH METALFLEX**

| DIA             | PART # | PRICE/FT |
|-----------------|--------|----------|
| 2"              | HMF02  | \$6.93   |
| 3"              | HMF03  | \$8.73   |
| 4"              | HMF04  | \$12.03  |
| 5"              | HMF05  | \$13.40  |
| 6"              | HMF06  | \$16.33  |
| 7"              | HMF07  | \$21.23  |
| 8"              | HMF08  | \$32.46  |
| 9"              | HMF09  | \$38.79  |
| 10"             | HMF10  | \$43.23  |
| PRICED PER FOOT |        |          |





ALL HOSE DIAMETER IS I.D.

Standard length(s) 5 ft, 10 ft, 25 ft Increments. Larger diameters available . Special crating required on 10 ft or longer pieces, 5" diameter & up

| GS HIGH TEM | Ρ |
|-------------|---|
|-------------|---|

| DIA             | PART # | PRICE/FT |
|-----------------|--------|----------|
| 2"              | HGS02  | \$15.63  |
| 3"              | HGS03  | \$20.15  |
| 4"              | HGS04  | \$23.84  |
| 5"              | HGS05  | \$28.44  |
| 6"              | HGS06  | \$32.80  |
| 8"              | HGS08  | \$42.87  |
| 10"             | HGS10  | \$51.68  |
| 12"             | HGS12  | \$64.27  |
| PRICED PER FOOT |        |          |

Part No. HGS00

GS

ALL HOSE DIAMETER IS I.D.

Standard length(s) 12 ft only

#### HOSE TO GATE CONNECTOR Hose to Gate Connector

| DIA  | PART # | PRICE   |
|------|--------|---------|
| 2.5" | HGC2.5 | \$5.04  |
| 3"   | HGC03  | \$5.53  |
| 4"   | HGC04  | \$5.68  |
| 5"   | HGC05  | \$5.97  |
| 6"   | HGC06  | \$6.31  |
| 7"   | HGC07  | \$6.89  |
| 8"   | HGC08  | \$7.77  |
| 10"  | HGC10  | \$11.54 |
| 12"  | HGC12  | \$13.65 |



- Interlocking galvanized steel
- Ideal for abrasive materials in grinding dusts, heavy wood chips
- Good for high temperature air handling applications, such as higher temperature engine exhaust.
- Good for dry bulk material transfer
- Temperature Range (°F) -10° to 400°
- Wall thickness .016 to .020

Applications:

- Surface grinding
- Welding exhaust
- Heavy wood chips
- Pallets, moulding machines
- Iron Oxide Red, double-ply silicone coated fiberglass fabric hose with spring steel wire helix & external filament fiberglass cord
- Ideal for abrasive materials in grinding dusts, heavy wood chips
- Good for high temperature air handling applications, such as higher temperature engine exhaust.
- Good for dry bulk material transfer
- Resistant to many oils, solvents, ozone, water fungus, alkalis
- Temperature Range (°F) -65° to 550°, Intermittent 600°

Applications:

- Plastic molding, High temp injection molding
- Foundries, brick kilns
- Paper mills
- Oven venting, exhaust systems
- Hot fumes
- Transmission cooling
- Used to provide an extended external lip for hose connection to a blast gate or ball joint



DIA



## TO ORDER - Please call 1-877-904-4022 or email sales@blastgateco.com